

UN324 - 300lb Nugget Ice Machine

Self Contained Undercounter Nugget with Storage

Features and Benefits

Reliability:

- Greaseless bearing for reduced maintenance
- Stainless steel evaporator for maximum durability
- 3 Year parts and labor warranty
- Designed, engineered, assembled in the USA

Ease of Use:

- External air filter for easy cleaning
- Unit specific QR code for quick access to service manuals and warranty history
- Slide back door allows easy access to ice in the bin
- Intuitive control panel allows for quick and easy operation
- Ice scoop and power cord included

Compact Design:

- Only 24" wide, the ice maker can be placed in the tightest locations
- Optional floor mount kit lowers height to 33.5"

High Production:

 Produces up to 340 lb (154 kg) per day and stores 80 lb (36 kg), meeting the ice demands for many different applications

Environmentally Friendly:

- Low Energy Consumption
- Non-ozone depleting R290 refrigerant



Sealed, Maintenance-Free Bearings Ensure Maximum Reliability and Contribute to a Long Machine Life



Front Accessible External Air Filter For Easy Cleaning



24 Hour Volume Production

Air Co	oled	Water Cooled		
70°F/21°C Ai 50°F/10°C Wat		70°F/21°C Air 90°F/32°C 50°F/10°C Water 70°F/21°C		
340/154 lb/kg	266/121 lb/kg	340/154 281/127 lb/kg lb/kg		



Chewable, slow-melting ice. Ideal for use in healthcare, foodservice and school applications.



3/4" x 5/16" x 3/8" (1.9 x 0.8 x 0.95 cm)







- 3 years parts and labor on all components.
- 5 years parts on the compressor.
- Warranty valid in North, South & Central America for commercial installations.
- Contact factory for warranty in other regions.
- Residential Applications: 1 year parts and labor





UN324 - 300lb Nugget Ice Machine


Self Contained Undercounter Nugget with Storage













Specifications

Model Number	Condenser Unit	Storage Capacity Ib/kg	Basic Electrical Volts/Hz/Phase	Max. Fuse Size or HACR Circuit Breaker (amps)	Min. Circuit Ampacity	Energy Consumption kWh/100 lb (45.4 kg) 90°F(32°C)/70°F(21°C)	Gallons/100 l Potable	r Usage lb (liters/45.4 kg) Condenser C)/70°F(21°C)	Energy Star®
UN324AX-1	Air	80/36	115/60/1	15	Cord	4.92	12.0/45.5	-	√.
UN324WX-1	1 Water	80/36	115/60/1	15	Cord	4.10	12.0/45.5	95	4



All Models

Dimensions (W x D x H):

Unit: 24" x 28.5" x 39" (61.0 x 72.4 x 99.1 cm)

Includes 6" (15.24 cm) adjustable legs

Shipping Carton: 28.75" x 38.65" x 39" (73.0 x 98.2 x 99.1 cm)

Shipping Weight: BTUs per hour: 210 lb / 95 kg 3,000

Model Number	Refrigerant	Refrigerant Charge (oz)	
UN324AX-1	R290	5.25	
UN324WX-1	R290	4.5	



Accessories

Model Number	Description
KLP8S KBC1 KUFM24	Kit, Leg 6", Stainless Steel Kit, Casters Floor mount kit. Lowers height to 33.5"



Operating Requirements

	Minimum	Maximum	
Air Temperatures	50°F (10°C)	100°F (38°C)	
Water Temperatures	40°F (4.4°C)	100°F (38°C)	
Water Pressures	20 PSIG (1.4 bar)	80 PSIG (5.5 bar)	
Electrical Voltage	-5%	+10%	

Specifications and design are subject to change without notice.

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details.





