MC330L - 1400lb Cube Ice Machine

Prodigy ELITE® Modular Cube Ice Machine

PRODIGY ELITE Eclipse®



Compatible with ICELINQ®

ENHANCED RELIABILITY

Integrated ICELINQ® App
Provides real-time diagnostics, access to settings and guided cleanings. The app also contains specific information for convenient maintenance.

Upgraded Sensors
Ice thickness and water sensor design enhances cleanability and amplifies durability.

Preservation Mode
Maximizes uptime and notifies users of potential issues.

EASE OF USE

AutoAlert™ Panel
The AutoAlert™ panel displays relevant machine status that is visible across the room. Now featuring an external bin full indicator light and easier to read 16-segment display.

CONVENIENT DESIGN

Remote Condenser and Compressor
Allows for higher capacities in smaller footprint, while minimizing heat and noise output.

WaterSense Adaptive Purge
Optimizes water consmption, keeping the machine cleaner and operating more efficiently.



The ICELINQ® app simplifies interaction with machine via Bluetooth® connection



Intelligent sensor technology maximizes efficiency and lowers operating costs

24 Hour Volume Production

MC330 1400lb		
70°F/21°C 50°F/10°C	Air Water	90°F/32°C 70°F/21°C
1311/595 lb/kg		1089/494 lb/kg

Modular Bin Options

Model Number*	Dimensions W" x D" x H"	Bin Application Capacity lb/kg	Finish	Ship Weight lb/kg
IOD200	30 x 31 x 35	-	Stainless Steel	235/107
IOD250	30 x 31 x 41	-	Stainless Steel	260/152
IDC255	30 x 30 x 40	255/116	Stainless Steel	350/159

* Contact Scotsman for bin top requirements.

Cube Ice

Common ice form, ideal for mixed drinks.



Small Cube
7/8" x 7/8" x 3/8"
(2.22 x 2.22 x .95 cm)



Medium Cube
7/8" x 7/8" x 7/8"
(2.22 x 2.22 x 2.22 cm)

Certification

AUDI CERTIFIED · REVIT BY Scotsman · DESIGNED ENGINEERED ASSEMBLED IN THE USA · ECO · ICELINQ · CERTIFIED ISO 9001:2015 · agion Nature's antimicrobial · cULus · NSF

Warranty

- 3 Years parts and labor on all components.
- 5 Years parts and labor on the evaporator.
- 5 Years parts on the compressor and condenser.
- Warranty valid in North, South & Central America for commercial installations.
- Contact factory for warranty in other regions.
- Residential Applications: 1 year parts and labor

MC330L - 1400lb Cube Ice Machine

Scotsman®


101 Corporate Woods Parkway, Vernon Hills, IL 60061

1-800-SCOTSMAN | Fax: 847-913-9844 | www.scotsman-ice.com | customer.relations@scotsman-ice.com

MC330L - 1400lb Cube Ice Machine

Prodigy ELITE® Modular Cube Ice Machine

MC330L - 1400lb Cube Ice Machine



Specifications

Model Number	Condenser Unit	Basic Electrical Volts/Hz/Phase	Max. Fuse Size or HACR Circuit Breaker (amps)	Circuit Wires	Min. Circuit Ampacity	Energy Consumption kWh/100 lb (45.4 kg) 90˚F(32˚C)/70˚F(21˚C)	Water Usage Gallons/100 lb (liters/45.4 kg) Potable 90˚F(32˚C)	Water Usage Gallons/100 lb (liters/45.4 kg) Condenser 70˚F(21˚C)
MC330SLX-1	-	115/60/1	15	2	Cord	4.55	-	-
-	ECC1200X-32	208-230/60/1	30	2	17.7	4.43	14.29/54.1	-

All Models

Dimensions (W x D x H):

MC330 Unit:	30" x 24" x 23" (76.2 x 61.0 x 58.4 cm)
Shipping Carton:	33.5" x 27.5" x 28" (85.1 x 70.0 x 71.1 cm)
Condenser Unit:	30" x 18" x 35" (76.2 x 45.7 x 88.9 cm)
Shipping Carton:	42" x 34" x 45" (106.7 x 86.4 x 114.3 cm)
Shipping Weight:	MC330xL 175 lb / 80 kg ECC1200 310 lb / 141 kg

BTUs per hour: 19,000 (MC330)

Model Number	Refrigerant	Refrigerant Charge (oz)
ECC1200X-32	R449A	248.0

Accessories

Model Number	Description
KSBU	Smart-Board™ Advanced Control - Use additional operational data for fast diagnosis.
KSBU-N	Smart-Board™ Advanced Control with Network - Network capable.
KVS	Vari-Smart Ice Level Control - Program ice levels to match ice needs
KBILC	Basic Ice Level Control - Thermistor technology, ideal for dispenser applications.
3BRTE20-EH	Line set, 20ft. Refrigerant and Brazing required
3BRTE35-EH	Line set, 35ft. Refrigerant and Brazing required
3BRTE50-EH	Line set, 50ft. Refrigerant and Brazing required
XR-30	XSafe® Sanitation System for Modular Cube - Continuous operation, field-installed.

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details.

Operating Requirements

	Minimum	Maximum
Air Temperatures	50°F (10°C)	100°F (38°C)
Water Temperatures	40°F (4.4°C)	100°F (38°C)
Remote Cond. Temps	-20°F (-29°C)	120°F (49°C)
Potable Water Pressure	20 PSIG (1.4 bar)	80 PSIG (5.5 bar)
Cond. Water Pressure	20 PSIG (1.4 bar)	230 PSIG (16.1 bar)
Electrical Voltage	-5%	+10%

Specifications and design are subject to change without notice.

101 Corporate Woods Parkway, Vernon Hills, IL 60061
1-800-SCOTSMAN | Fax: 847-913-9844 | www.scotsman-ice.com
customer.relations@scotsman-ice.com

© 2026 Scotsman Ice Systems.

WELBILT an Ali Group Company

Scotsman®