

#### UC2724 - 270 lb Cube Ice Machine

Self-Contained Undercounter Ice Machine with Storage

### **Features and Benefits**

#### **Space Saving Design:**

- Only 24" wide, this ice maker can be placed it the tightest locations
- Front breathing No side clearance required for flexible placement
- Recessed utility chase provides clearance for tight installs
- Optional floor mount kit lowers height to 33.5"

#### Ease of Use:

- Removable external air filter for easy cleaning
- Unit specific QR code for quick access to service manuals, cleaning guides and warranty history
- Ergonomic slide back door allows easy access to ice in the bin
- Power cord, NEMA 5-15P plug, ice scoop and adjustable legs are included for quick and easy installation

#### Reliability:

- Heavy duty, rust-free front panel and corrosion-resistant aluminum alloy side panels for maximum lifespan
- 3 Year parts and labor warranty
- Designed, engineered and assembled in the USA

#### **High Production:**

• Produces up to 282 lb (128 kg) per day and stores 80 lb (36 kg), maximizing ice output despite its small footprint

#### **Environmentally Friendly:**

- Low Energy Consumption
- Non-ozone depleting R290 refrigerant





Front Accessible External Air Filter for Easy Cleaning



Recessed Utility Chase Provides Clearance for Tight Installs



Ergonomic Slide Back Door Allows Easy Access to Ice in the Bin



Unit Specific QR Code for Quick Access to Service Manuals, Cleaning **Guides and Warranty History** 



### 24 Hour Volume Production

Air Cooled			Water Cooled			
70°F/21°C 50°F/10°C	Air Water	90°F/32°C 70°F/21°C	70°F/21°C 50°F/10°C	Air Water	90°F/32°C 70°F/21°C	
282/128 lb/kg		202/92 lb/kg	282/128 lb/kg		232/105 lb/kg	



Small Cube 7/8" x 7/8" x 3/8"

Medium Cube 7/8" x 7/8" x 7/8" (2.22 x 2.22 x .95 cm) (2.22 x 2.22 x 2.22 cm)



EUSA

### Certification



















- 3 years parts and labor on all components
- 5 years parts on the compressor
- Warranty valid in North, South & Central America for commercial installations
- Contact factory for warranty in other regions • Residential Applications: 1 year parts and labor




### Self-Contained Undercounter Ice Machine with Storage









Front Breathing and No Side Clearance Required, Allowing for Flexible Placement









## **Specifications**

	Model Number Cube Size: medium or small	Condenser Unit	Storage Capacity Ib/kg	Basic Electrical Volts/Hz/Phase	Max. Fuse Size or HACR Circuit Breaker (amps)	Circuit Wires	Min. Circuit Ampacity	Energy Consumption kWh/100 lb (45.4 kg) 90°F(32°C)/70°F(21°C)	Gallons/100 lk Potable	Usage o (liters/45.4 kg) Condenser )/70°F(21°C)
ı	∃	Air	80/36	115/60/1	15	2	Cord	6.47	23.8/90.6	-
l	B UC2724MWX-1	Water	80/36	115/60/1	15	2	Cord	5.11	26.1/99.4	136/515
ı	, Γ UC2724SAX-1	Air	80/36	115/60/1	15	2	Cord	6.47	23.8/90.6	-
/	UC2724SWX-1	Water	80/36	115/60/1	15	2	Cord	5.11	26.1/99.4	136/515



## **All Models**

#### Dimensions (W x D x H):

Unit: 24" X 28.5" X 39"

(61.0 x 72.4 x 99.1 cm)

Height includes 6" (15.24 cm) adjustable legs

Shipping Carton: 29" x 39" x 39"

(73.7 x 99.1 x 99.1 cm)

Shipping Weight: 175 lb / 79.4 kg BTUs per hour: 5,000

Model Number	Refrigerant	Refrigerant Charge (oz)
UC2724MAX-1	R290	4.75
UC2724MWX-1	R290	4.5
UC2724SAX-1	R290	4.75
UC2724SWX-1	R290	4.5



# Accessories

Model Number	Description
KLP8S	Kit, Leg 6", Stainless Steel
KBC1	Kit, Casters
KUFM24	Floor mount kit. Lowers height to 33.5"

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details



# **Operating Requirements**

	Minimum	Maximum	
Air Temperatures	50°F (10°C)	100°F (38°C)	
Water Temperatures	40°F (4.4°C)	100°F (38°C)	
Water Pressures	20 PSIG (1.4 bar)	80 PSIG (5.5 bar)	
Electrical Voltage	-5%	+10%	

Specifications and design are subject to change without notice





