Scotsman° UNDERCOUNTER UNITS

UF2020 - 200 lb Flake Ice Machine

Self-Contained Undercounter Ice Machine with Storage



Sealed, maintenance-free bearings ensure maximum reliability and contribute to a long machine life



Unit specific QR code for quick access to service manuals, cleaning guides and warranty history

Features and Benefits

Reliability:

- Sealed, maintenance-free bearings for reduced preventative maintenance and long-lasting performance
- Stainless steel evaporator and auger for maximum durability
- Heavy duty, rust-free front panel and corrosion-resistant aluminum alloy side panels for maximum lifespan
- 3 Year parts and labor warranty
- Designed, engineered and assembled in the USA

Space Saving Design:

- Only 20" wide, this ice maker can be placed it the tightest locations
- Front breathing No side clearance required for flexible placement
- Optional floor mount kit allows for installation under 34" ADA counter tops

Ease of Use:

- Unit specific QR code for quick access to service manuals, cleaning quides and warranty history
- Ergonomic slide back door allows easy access to ice in the bin
- Power cord, NEMA 5-15P plug, ice scoop and adjustable legs are included for quick and easy installation

High Production:

 Produces up to 216 lb (98 kg) per day and stores 57 lb (26 kg), maximizing ice output despite its small footprint

Environmentally Friendly:


- Energy Star certified
- Meets US Safe Drinking Act low lead requirements
- Non-ozone depleting R290 refrigerant



Ergonomic slide back door allows easy access to ice in the bin



ADA compliant with optional floor mount kit










- 3 years parts and labor on all components
- Warranty valid in North, South & Central America for commercial installations
- Contact factory for warranty in other regions
- Residential Applications: 1 year parts and labor



- 101 Corporate Woods Parkway, Vernon Hills, IL 60061 •
- 1-800-SCOTSMAN Fax: 847-913-9844 www.scotsman-ice.com customer.relations@scotsman-ice.com •








Front breathing and no side clearance required, allowing for flexible placement

Recommended Minimum Clearance:

Side: 1/8" Top: 1/4" Back: 4"









Specifications

Model Number	Condenser Unit	Storage Capacity Ib/kg	Basic Electrical Volts/Hz/Phase	Max. Fuse Size or HACR Circuit Breaker (amps)	Circuit Wires	Min. Circuit Ampacity	Energy Consumption kWh/100 lb (45.4 kg) 90°F(32°C)/70°F(21°C)	Potable Water Usage Gallons/100 lb (liters/45.4 kg) 90°F(32°C)/70°F(21°C)
UF2020AX-1	Air	57/26	115/60/1	15	2	Cord	4.63	12/45.5



All Models

Dimensions (W x D x H):

20" X 24" X 38"

(50.8 x 61.0 x 96.5 cm)

Includes 6" (15.24 cm) adjustable legs

22" x 27" x 38" Shipping Carton:

(55.9 x 68.6 x 96.5 cm)

Shipping Weight: 129 lb / 59 kg 4,100 BTUs per hour: Refrigerant: R290 Refrigerant Charge (oz): 3.00



Accessories

Model Number	Description	
KLP8S	Kit, Leg 6", Stainless Steel	
KBC1	Kit, Casters	
KUFM20	For ADA applications. Floor mount kit lowers overall height to 31.9"	

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details.



Operating Requirements

	Minimum	Maximum		
Air Temperatures	50°F (10°C)	100°F (38°C)		
Water Temperatures	40°F (4.4°C)	100°F (38°C)		
Water Pressures	20 PSIG (1.4 bar)	80 PSIG (5.5 bar)		
Electrical Voltage	-5%	+10%		

Specifications and design are subject to change without notice.



- 1-800-SCOTSMAN Fax: 847-913-9844
- www.scotsman-ice.com customer.relations@scotsman-ice.com





