



N2030 - 2000lb Nugget Ice Machine

Prodigy Plus® Nugget Ice Machine




Features & Benefits

- Available in softer, Original Chewable Nugget Ice or harder, H2 Nugget Ice
- Sealed, maintenance-free bearings for reduced preventative maintenance and long-lasting performance
- Stainless steel evaporator and auger for maximum durability
- AutoAlert™ indicator lights for better visibility
- Operational footprint among the industry's smallest
- Unit specific QR code for quick access to service manuals, cleaning guides and warranty history
- Extra large production capacity in a small footprint
- Smart-Board™ advanced feature module available for additional diagnostic capabilities
- Optional Vari-Smart™ ice level control allows operators to customize ice levels
- Antimicrobial protection guards internal surfaces between cleanings



Sealed, Maintenance-Free Bearings Ensure Maximum Reliability and Contribute to a Long Machine Life



Available in Softer, Original Chewable Nugget Ice or Harder, H² Nugget Ice



24 Hour Volume Production

Original Chewable Nugget

Remote Cooled		Water Cooled	
70°F/21°C	Air	90°F/32°C	70°F/21°C
50°F/10°C	Water	50°F/10°C	70°F/21°C
2008/913	lb/kg	1652/749	lb/kg



24 Hour Volume Production

H² Nugget

Remote Cooled

70°F/21°C	Air	90°F/32°C
50°F/10°C	Water	70°F/21°C
1916/869	lb/kg	1667/756



Modular Bin Options

Model Number*	Dimensions W" x D" x H"	Bin Application Capacity lb/kg	Finish	Ship Weight lb/kg
BL1048S	48 x 31 x 54.4	1000/454		268/122
BL1360S	60 x 61 x 54.4	1320/599		322/147
BL1660S	60 x 31 x 63.4	1660/753		340/154

*Contact Scotsman for bin top requirements.



Nugget Ice



Original Chewable Nugget
Ice Hardness Rating: Soft = 74%
Dimensions: 3/16" x 3/16" x 3/8"



H² Nugget
Ice Hardness Rating: Hard = 87%
Dimensions: 3/8" x 3/8" x 3/8"



Certification



Warranty

- 3 years parts and labor on all components.
- 5 years parts on the compressor.
- Warranty valid in North, South & Central America for commercial installations.
- Contact factory for warranty in other regions.
- Residential Applications: 1 year parts and labor

Scotsman®


101 Corporate Woods Parkway, Vernon Hills, IL 60061

1-800-SCOTSMAN | Fax: 847-913-9844 | www.scotsman-ice.com | customer.relations@scotsman-ice.com

N2030 - 2000lb Nugget Ice Machine

N2030 - 2000lb Nugget Ice Machine

Prodigy Plus® Nugget Ice Machine



Specifications

Model Number	Condenser Unit	Basic Electrical Volts/Hz/Phase	Max. Fuse Size or HACR Circuit Breaker (amps)	Circuit Wires	Min. Circuit Ampacity	Energy Consumption kWh/100 lb (45.4 kg) 90°F(32°C)/70°F(21°C)	Water Usage Gallons/100 lb (liters/45.4 kg)	
							Potable 90°F(32°C)/70°F(21°C)	Condenser 90°F(32°C)/70°F(21°C)
soft	NS2030RX-32	Remote	208-230/60/1	50	2	34.3	12.0/45.5	-
	NS2030RX-3	Remote	208-230/60/3	35	3	21.9	12.0/45.5	-
	NS2030WX-32	Water	208-230/60/1	50	2	32.1	12.0/45.5	79.1/299
	NS2030WX-3	Water	208-230/60/3	30	3	19.7	12.0/45.5	79.1/299
hard	NH2030RX-32	Remote	208-230/60/1	50	2	34.3	12.0/45.5	-



All Models

Dimensions (W x D x H):

Unit: 30" x 24" x 29"
(76.2 x 61.0 x 74.0 cm)

Shipping Carton: 33.5" x 27.5" x 34"
(85.1 x 69.9 x 86.4 cm)

Shipping Weight: 350 lb / 159 kg
BTUs per hour: 24,400

Model Number	Refrigerant	Refrigerant Charge (oz)
NS2030RX-32	R449A	240.0
NS2030RX-3	R449A	240.0
NS2030WX-32	R449A	58.0
NS2030WX-3	R449A	58.0
NH2030RX-32	R449A	240.0



Accessories

Model Number	Description
ERC611X-32	Remote condenser for N2030RX, 208-230V/60/1
BRT10	Line set, 10ft, brazing required.
BRT25	Line set, 25ft, brazing required.
BRT40	Line set, 40ft, brazing required.
BRT75	Line set, 75ft, brazing required.
KVS	Vari-Smart™ Ice Level Control - Program ice bin levels to match ice needs.
KSBU	Smart-Board™ Advanced Control - Use additional operational data for fast diagnosis.
KSBU-N	Smart-Board™ Advanced Control with Network - Network capable.
KPAS	Prodigy Advanced Sustainability Kit - Includes KVS and KSBU - N

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details.



Operating Requirements

	Minimum	Maximum
Air Temperatures	50°F (10°C)	100°F (38°C)
Water Temperatures	40°F (4.4°C)	100°F (38°C)
Remote Cond. Temps	-20°F (-29°C)	120°F (49°C)
Water Pressures	20 PSIG (1.4 bar)	80 PSIG (5.5 bar)
Electrical Voltage	-5%	+10%

Specifications and design are subject to change without notice.